

AgriShift MLM-B 120V 10W EB GEN 3



- *Reduce stress for animals, increase Animal Welfare*
- *Built for Barn*
- *Durability and robustness to withstand pressure washing and dirt*
- Easy of installation

Introduce your poultry to animal-centric lighting

The AgriShift[®] MLM-B is an animal welfare-friendly lighting solution made to meet a birds' developmental needs at every stage of growth. Designed with Dim-to-Blue[®] technology, it optimizes performance by providing a species-specific spectrum shown to naturally calm chickens, minimizing aggressive behaviors.

The AgriShift[®] MLM-B has an enhanced blue and green spectrum

with added red content for early bird development. Green light increases growth during early stages of development, while blue light is shown to be helpful in the growth of poultry at a later age by elevating plasma androgens. Other studies show that blue light keeps birds calm, reduces corticosterone levels and heterophil:lymphocyte ratios—blood markers for short- and long-term stress and positively affects blood glucose and triglyceride levels.

Specifications and Ordering

AgriShift MLM-B 120V 10W EB GEN 3

Nominal power	10W
Luminous flux - human photopic	1000 lm
Luminous flux - animal photopic	-
Luminous Flux melonopic	-
Initial LED luminaire efficacy	100 lm/W
Input voltage	120VAC
Input frequency	60 Hz
Driver included	Yes
Surge protection	MOV/FUSE
Power consumption tolerance	+/-5%
Power factor	0.98
Beam angle	Very Wide
Beam spread	-
Driver failure rate at 50K hrs	<5%
Warranty period	5 years
Recyclable	No
HS code	8539.52.0091
Country of origin	Peoples Republic of China

Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 1%
Spectral output	4700K

Operating and Mechanical Specifications


Operating temperature	-20°C to 40°C / -4°F to 104°F
Rated life	>50,000 hours
Lens material	PC
Housing material	PC/AL
Diameter	81mm
Height	143mm
Length	-
Width	-
Mount / Adaptor	E26 Edison Base
Connection	Edison Base E26/E27 Connection
Control interface	Phase cut
Product weight per piece	0.177kg/0.390Lbs

Safety and Certifications

CE Mark	-
RoHS Compliant	Yes
ANSI/UL	Yes
Can/CSA STD C22.2 NO 250.0	Yes
CB	-
Flammability mark	-
ECO energy classification	-
IEC protection class	Class I
IK impact rating	IK07
IP code	IP66

Ordering Information

Description	SKU
MLM 1000/WB20 120V EB/T VWB Gen 3	1000000805
MLM 1000/WB20 120V JB/T VWB Gen 3	1000000871
MLM 1000/WB20 120V JJ/T VWB Gen 3	1000000872
MLM 1000/WB20 120V HW/T VWB Gen 3	1000000873



Contact us

or learn more at:

www.once.lighting

3955 Annapolis Ave N, Suite 100

Plymouth, MN 55447

United States of America

P +1 (763) 381-5621

info@onceteam.com

Am Südfeld 7

49377 Vechta

Germany

P +49 (0) 4441-8898-10

info.germany@onceteam.com

once
by  **signify**

© 2021 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 5/2021 Data subject to change