

AgriShift[®] TLUS Bright Gen 3 Under-System Tube Light for Layer



- *Reduction in floor eggs*
- *Fully dimmable simulation improves animal welfare*
- *High energy efficiency: up to 140 lm/w*
- *High number of tube segments which can be connected in a line*
- *Both in-series and stringer tube version enable installation flexibility*

Introduce your layer to animal-centric lighting

Experience reduction in floor eggs with Agrishift TLUS Bright Gen3 under system lighting solution. TLUS Bright Gen3 solution provides continuously bright and uniform lighting under system solution free of dark spots and shadows. With our lighting solution, birds are less likely to lay egg under cage systems, while being noticeably calmer. In addition, TLUS Bright Gen3 offers ease and flexibility of installation by having both in-series and stringer versions and all necessary accessories. Save on energy costs with high energy efficiency of TLUS Bright Gen3.

Specifications and Ordering

AgriShift® TLUS Bright Gen 3 Specifications

Nominal power	4.2 W
Luminous flux - human photopic	600 lm
Luminous flux - animal photopic	-
Luminous Flux melonopic	-
Initial LED luminaire efficacy	140 lm/W
Input voltage	120VAC
Input frequency	60 Hz
Driver included	Yes
Surge protection	MOV/FUSE
Power consumption tolerance	+/-10%
Power factor	0.98
Beam angle	Very Wide
Beam spread	Dual asymmetric
Driver failure rate at 50K hrs	<5%
Warranty period	5 Years
Recyclable	No
HS code	8539.52.0051
Country of origin	Peoples Republic of China

Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 1%
Colour temperature (K)	5000K

Operating and Mechanical Specifications

Operating temperature	-20°C to 40°C / -4°F to 104°F
Rated life	>50,000 hours
Lens material	PC
Housing material	PC
Diameter	25.6mm
Height	-
Length	55in (1397mm)
Width	-
Mount / Adaptor	Clips
Connection	Starter/extension cable
Control interface	Phase Cut
Product weight per piece	0.778lb (0.353kg)

Safety and Certifications

CE Mark	-
RoHS Compliant	Yes
ANSI/UL	Yes
Can/CSA STD C22.2 NO 250.0	Yes
CB	-
Flammability mark	-
ECO energy classification	-
IEC protection class	Class I
IK impact rating	IK03
IP code	IP66

Ordering Information

Description	SKU
TLUS 620/W50 120V 1T/055 WB Gen 3	1000000952

Contact us

or learn more at:

www.once.lighting

3955 Annapolis Ave N, Suite 100

Plymouth, MN 55447

United States of America

P +1 (763) 381-5621

info@onceteam.com

Am Südfeld 7

49377 Vechta

Germany

P +49 (0) 4441-8898-10

info.germany@onceteam.com

once
by  **signify**

© 2021 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 4/2021 Data subject to change