

DOME PRO Junglite (DOME 1250/WG30 230V VWB)



- Robust lighting solution built for barn
- Excellent light for broilers, pullets and turkeys
- Improve animal health and welfare with our patented Junglite Green lighting
- No flicker, even when dimming below 5%
- Highly efficient LED with lifetime >50,000 hours
- Optimal light distribution with wide beam angle


Invest in the quality of your lighting system

Our range of Dome luminaires are designed to withstand harsh barn environments. The wide beam angle, in combination with the luminous flux, make that the Dome is luminaire that can be applied in a wide range of general lighting applications. Dome Pro Junglite Green provides poultry specific lighting color, that improves bird health and welfare. At high intensity, this reflects very cool white, when dimmed this moves to the Junglite Green spectrum.


The Dome Pro Junglite Green is perfectly dimmable and flicker free, to ensure an optimum bird performance under our lighting. The luminaire is easy to install, and connects to the ONCE IUL-base units. These can be mounted in multiple ways.

We advice to use this product in combination with our EPU-1500 dimmer, in order to get the perfect dimming behavior that is required.

Dimensions



Beam Spread



Visit our website for more information: www.once.lighting

Specifications and Ordering

DOME 1250/WG30 230V VWB Specifications

Nominal power	11W
Luminous flux - human photopic	1200 lm
Luminous flux - poultry photopic	-
Initial LED luminaire efficacy	110 lm/W
Input voltage	220-240V
Input frequency	50/60 Hz
Driver included	Yes
Surge protection	-
Inrush current	3.5A
Inrush time	40µs
Power consumption tolerance	+/- 10%
Power factor	0.98
Beam angle	Very wide beam
Warranty period	3 Years
HS code	85395200
Country of origin	Republic of Poland

Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100 % to 1%
Colour temperature (K)	7900K
CRI	>80
Flicker index [Pst]	<1
Stroboscopic effect [SVM]	0.03
Colour consistency [SDCM]	-

Operating and Mechanical Specifications

Operating temperature	-10°C – 40°C / 14°F - 104°F
Lumen maintenance L70B50 [h]	>50,000 hours
Lens material	PMMA
Housing material	PC
Diameter	145mm
Height	87mm
Length	-
Width	-
Mount / Adaptor	IUL base
Connection	Push in connector
Control interface	ONCE digital dimming
Product weight per piece	0.244kg/0.538Lbs

Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	-
CB	-
Flammability mark	-
EU energy classification rating	Exempt
IEC protection class	Class II
IK impact rating	IK03
IP Code	IP66

Ordering Information

Description	SKU	Order code
DOME 1250/WG30 230V VWB	1000000923	929002100481

**Contact us
or learn more at:**
www.once.lighting

ONCE Innovations Inc

3955 Annapolis Ave N, Suite 100
Plymouth, MN 55447
P +1(763) 297 9163

ONCE GmbH

Vechtaer Marsch 3
49377 Vechta, Germany
P +49 (0)4441 8898-10

Email: once.info@signify.com



© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change