



Reflector Infrared BR40,PAR38

175PAR38/HEAT/CL 120V 12/1

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. Philips Infrared lamps are suited for heating and drying in industrial and commercial aplications. These incandescent, gas-filled infrared heat lamps come up to full temperature almost immediately, eliminating costly warm-up time. Highly efficient heat generators that produce a minimum of light rays and a high amount of infrared radiation. The BR40 lamp provides a built-in reflector for radiant energy control.

Product data


| General Information | | | |
|--------------------------|--|--|--|
| Cap-Base | E26/50X39 [Skirted Medium Screw (PAR Lamps)] | | |
| Operating Position | UNIVERSAL [Any or Universal (U)] | | |
| Nominal lifetime | 5,000 hour(s) | | |
| Rated Lifetime (Hours) | 5,000 hour(s) | | |
| Lighting Technology | Incandescent | | |
| | | | |
| Light Technical | | | |
| Color Designation | С | | |
| | | | |
| Operating and Electrical | | | |
| Power Consumption | 175 W | | |
| Voltage (Nom) | 115-125 V | | |
| | | | |
| Controls and Dimming | | | |
| Dimmable | Yes | | |
| | | | |
| Mechanical and Housing | | | |
| Bulb Finish | Clear | | |

| Bulb Material | Hard Glass | | |
|---------------------------------|----------------------------|--|--|
| Bulb Shape | PAR38 | | |
| | | | |
| Product Data | | | |
| Order product name | 175PAR38/HEAT/CL 120V 12/1 | | |
| Full product name | 175PAR38/HEAT/CL 120V 12/1 | | |
| Full product code | 904667711626215 | | |
| Order code | 923813534608 | | |
| Material Nr. (12NC) | 923813534608 | | |
| Numerator - Quantity Per Pack | 1 | | |
| Net Weight (Piece) | 308.000 g | | |
| EAN/UPC - Product/Case | 046677116262 | | |
| Numerator - Packs per outer box | 12 | | |
| EAN/UPC - Case | 50046677145519 | | |

Datasheet, 2024, June 18 data subject to change

Reflector Infrared BR40, PAR38

Dimensional drawing



| Product | D | C (max) | C1 (max) |
|----------------------------|--------|---------|----------|
| 175PAR38/HEAT/CL 120V 12/1 | 121 mm | 135 mm | 123 mm |

