


ND-DOME 900/MS30 120V IA1 RWB\*



- *No flicker, even when dimming below 5% because of DC conversion inside of the luminaire*
- *Wireless lighting with remote monitoring app*
- *Dynamic spectrum directs desirable behaviors in animals and can be adjusted to improve welfare*
- *Highly efficient LED with lifetime >50,000 hours*
- *Optimal light distribution*

\*RWB—Red/White/Blue

Optimized for egg layers

## Introducing a dynamic lighting solution


Improve animal welfare while experiencing optimal results with the ND-DOME 900/MS30 120V IA1 VWB NatureDynamics Dome. This customizable LED-based luminaire features an advanced and intuitive light spectrum that is designed to meet the individual needs of every species at all stages of growth.

With this new, revolutionary and future-proof lighting solution, farmers now have maximum zoning flexibility and easy light recipe management through an app-based platform. By utilizing our scientifically proven light recipes (spectrum, intensity and schedule) the ideal lighting to solve daily challenges, improve animal welfare and achieve optimal results is a touch away.


---

Visit our website for more information: [www.once.lighting](http://www.once.lighting)

## Beam Spread



## Dimensions



# Specifications and Ordering

## ND-DOME 900/MS30 120V IA1 VWB Specs

Nominal power	12W
Luminous flux - human photopic	1100 lm
Luminous flux - poultry photopic	-
Luminous Flux melonopic	-
Initial LED luminaire efficacy	92 lm/W
Input voltage	120 VAC
Input frequency	60 Hz
Driver included	Yes
Surge protection	MOV/FUSE
Inrush current	1.7A
Inrush time	40µs
Power consumption tolerance	+/- 10%
Power factor	0.9
Beam angle	Very Wide
Beam spread	Dual asymmetric
Driver failure rate at 50k hrs	<5%
Warranty period	5 years
Recyclable	No
HS code	9405.42.6000
Country of origin	Poland

## Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 0%
Spectral output	Tunable
CRI	90

## Operating and Mechanical Specifications

Operating temperature	-10°C to 40°C / 14°F to 104°F
Rated Life	>50,000 hours
Lens material	PC
Housing material	PC
Diameter	145mm
Height	87mm
Length	-
Width	-
Mount / Adaptor	ND DOME JB Adapter
Connection	Junction Box + Adapter ND Drop Cord HW
Control interface	Philips Gateway, ZigBee controlled PWM
Product weight per piece	0.244 Kg / 0.538 Lbs

## Safety and Certifications

CE Mark	-
RoHS Compliant	Yes
ANSI/UL	Yes
Can/CSA STD	Yes
Flammability mark	-
ECO energy classification	-
IEC protection class	Class II
IK impact rating	IK07
IP Code	IP65

## Ordering Information

Description	SKU	Order code
ND-DOME 900/MS30 120V IA1 VWB	1000000967	929002100648

## Chromaticity

## Contact us

or learn more at:

[www.once.lighting](http://www.once.lighting)

15255 23rd Ave. N.	Am Südfeld 7
Plymouth, MN 55447	49377 Vechta
United States of America	Germany
P +1 (763) 381-5621	P +49 (0) 4441-8898-10
info@onceteam.com	info.germany@onceteam.com



© 2021 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 2/2021 Data subject to change