

ND-DOME 900/MS40 230V IA1 VWB




- *Multispectral light*
- *Excellent light distribution*
- *Support to the circadian rhythm of the animal*
- *Perfect resemblance to a natural light spectrum*
- *Ability to attune to the needs of every animal*

Introducing a dynamic lighting solution


Improve animal welfare while experiencing optimal results with the ND-DOME 900/MS40 230V IA1 VWB NatureDynamics Dome. This customizable LED-based luminaire features an advanced and intuitive light spectrum that is designed to meet the individual needs of every species at all stages of growth.

With this new, revolutionary and future-proof lighting solution, farmers now have maximum zoning flexibility and easy light recipe management through an app-based platform. By utilizing our scientifically proven light recipes (spectrum, intensity and schedule) the ideal lighting to solve daily challenges, improve animal welfare and achieve optimal results is a touch away.

Dimensions



Beam Spread



Visit our website for more information: www.once.lighting

Specifications and Ordering

ND-DOME 900/MS40 230V IA1 VWB Specs

Nominal power	12W
Luminous flux - human photopic	1100 lm
Luminous flux - poultry photopic	-
Luminous Flux melonopic	-
Initial LED luminaire efficacy	92 lm/W
Input voltage	220-240 VAC
Input frequency	50/60 Hz
Driver included	Yes
Surge protection	-
Inrush current	3.5A
Inrush time	40µs
Power consumption tolerance	+/- 10%
Power factor	0.98
Beam angle	Very wide beam
Beam spread	-
Driver failure rate at 50k hrs	-
Warranty period	3 years
Recyclable	-
HS code	85395200
Country of origin	Republic of Poland

Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 1%
Colour temperature (K)	RWB Dim-to-Red optimized

Operating and Mechanical Specifications

Operating temperature	-10°C to 40°C / 14°F to 104°F
Rated Life	>50,000 hours
Lens material	PMMA
Housing material	PC
Diameter	14.9cm
Height	9.4cm
Length	-
Width	-
Mount / Adaptor	IUL Base
Connection	Push in connector
Control interface	ZigBee
Product weight per piece	0.22 Kg / 0.495 Lbs

Safety and Certifications

CE Mark	Yes
RoHS Compliant	Yes
ANSI/UL	-
CB	-
Flammability mark	-
ECO energy classification	-
IEC protection class	Class II
IK impact rating	IK03
IP Code	IP66

Ordering Information

Description	SKU	Order code
ND-DOME 900/MS40 230V IA1 VWB	1000000966	N/A

Spectrum

Our Junglite Green technology targets poultry-specific color sensitivities to benefit all growth stages.



Contact us

or learn more at:

www.once.lighting

15255 23rd Ave. N.

Plymouth, MN 55447

United States of America

P +1 (763) 381-5621

info@onceteam.com

Am Südfeld 7

49377 Vechta

Germany

P +49 (0) 4441-8898-10

info.germany@onceteam.com

once
by  **signify**

© 2021 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 2/2021 Data subject to change