

## SILOX-PRO-120-Junglite Green




- *Easy retrofit solution with wide beam angle*
- *Improve animal welfare with natural sunrise/sunset simulation*
- *Calm flock and improve feed conversion rates with species-specific Junglite Green technology*
- *Durable and quality tube light solution*

## Introduce your animals to species-specific lighting


Designed to influence desirable physiological and biological processes in animals, the SILOX-PRO-120 with Junglite Green technology features a species-specific spectrum to improve both your return on investment and the animals' wellbeing.

The SILOX-PRO-120-Junglite Green offers total dimmability, high efficiency, energy savings, maximum durability, uniform light distribution and more. Pair with any of our ITF enclosures for a high protection grade (IP67),

### Dimensions



### Beam Spread



# Specifications and Ordering

## SILOX-PRO-120-Junglite Green Specifications

Nominal power	18.5W
Luminous flux - human photopic	2000 lm
Luminous flux - poultry photopic	-
Initial LED luminaire efficacy	110 lm/W
Input voltage	230V
Input frequency	50/60 Hz
Driver included	Yes
Surge protection	-
Inrush current	8.8A
Inrush time	300µs
Power consumption tolerance	+/- 10%
Power factor	0.86
Beam angle	145°
Warranty period	3 Years
HS code	85395000
Country of origin	Federal Republic of Germany

## Ordering Information

Description	SKU	Order code
SILOX-PRO-120-Junglite Green	1000000105	NA

## Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 1%
Colour temperature (K)	Green/blue + red
CRI	>80
Flicker index [Pst]	0.01
Stroboscopic effect [SVM]	-
Colour consistency [SDCM]	Exempt

## Operating and Mechanical Specifications

Operating temperature	-10°C – 40°C / 14°F - 104°F
Lumen maintenance L70B50 [h]	>50,000 hours
Lens material	PC/PMMA
Housing material	Aluminum + PC
Diameter	25mm / 1 in (T8)
Height	-
Length	1200mm / 4 ft
Width	-
Mount / Adaptor	G13 rotatable base
Connection	T8-G13
Control interface	Trailing edge dimming / ONCE digital dimming protocol
Product weight per piece	0.58Kg / 1.27 Lbs pc.

## Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	-
CB	-
Flammability mark	-
EU energy classification rating	Exempt
IEC protection class	Class II
IK impact rating	Based on enclosure
IP Code	Based on enclosure

### Contact us

or learn more at:

[www.once.lighting](http://www.once.lighting)

### ONCE Innovations Inc

3955 Annapolis Ave N, Suite 100  
Plymouth, MN 55447  
P +1(763) 297 9163

### ONCE GmbH

Vechtaer Marsch 3  
49377 Vechta, Germany  
P +49 (0)4441 8898-10

Email: [once.info@signify.com](mailto:once.info@signify.com)

**once**  
by signify

© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change