

TULEX-HO-120 Junglite Green



- Innovative tube light with wide beam angle
- Improve animal welfare with species-specific Junglite Green technology
- Brighter light output illuminates spaces where it's needed most
- Durable and sustainable lighting solution


Introduce your animals to speciesspecific lighting


Beam Spread

Made with a brighter light output, the TULEX-HO-120 with Junglite Green technology is designed to replicate a birds' natural habitat. By simulating an enhanced green, with added blue, light spectrum, healthy growth and sexual development in poultry is encouraged. The TULEX-HO-120 features full dimming and

programming capabilities, which allows for reduced stress and lower mortality rates, while improving immune response in birds oftentimes caused by sudden changes in light. It offers optimal durability, uniform light distribution, high efficiency and more.

Dimensions





Visit our website for more information: www.once.lighting

Specifications and Ordering

TULEX-HO-120 Junglite Green Specifications

Nominal power	20W
Luminous flux - human photopic	2050 lm
Luminous flux - poultry photopic	-
Initial LED luminaire efficacy	102 lm/W
Input voltage	48VDC
Input frequency	DC
Driver included	No
Surge protection	-
Inrush current	-
Inrush time	-
Power consumption tolerance	+/- 10%
Power factor	-
Beam angle	145°
Warranty period	3 years
HS code	85395000
Country of origin	People's Republic of China

Ordering Information

Description	SKU	Order code
TULEX-HO-120 Junglite Green	1000000718	
TULEX-HO-120 Junglite Green (10 pcs)		929002100598

Spectral Output and Dimming Specifications

to 1%
te green
pt

Operating and Mechanical Specifications

Operating temperature	-10°C to 40°C / 14°F to 104°F
Lumen maintenance L70B50 [h]	>50,000 hours
Lens material	PC/PMMA
Housing material	PC/PMMA
Diameter	16mm
Height	-
Length	1270mm (1900mm with cable)
Width	-
Mount / Adaptor	Steel wire using fixing clamps
Connection	Cables with snap-in connectors
Control interface	PWM
Product weight per piece	0.41 Kg / 0.90 Lbs pc.

Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	-
СВ	Yes
Flammability mark	НВ
EU energy classification rating	Exempt
IEC protection class	Class III
IK impact rating	IK03
IP Code	IP69

Contact us or learn more at: www.once.lighting

ONCE Innovations Inc

3955 Annapolis Ave N, Suite 100 Plymouth, MN 55447 P +1(763) 297 9163

ONCE GmbH

Vechtaer Marsch 3 49377 Vechta, Germany P +49 (0)4441 8898-10

Email: once.info@signify.com



© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change