

#### TULEX-180-BASIC-AMBER




- Easy to install with quick connectors
- Improve animal welfare with full dimming and programming capabilities
- Innovative tube light with wide beam angle
- Durable and sustainable lighting solution

# Invest in the quality of your lighting system

The TULEX-180-BASIC-AMBER is made with a durable, Built-For-Your—Barn design and many easy-to-install features. It provides animals with warm white illumination and offers full dimming and programming capabilities, uniform light distribution and more.

#### **Dimensions**



Visit our website for more information: www.once.lighting

### Specifications and Ordering

#### **TULEX-180-BASIC-AMBER Specifications**

Nominal power	4W
Luminous flux - human photopic	320 lm
Luminous flux - poultry photopic	-
Initial LED luminaire efficacy	80 lm/W
Input voltage	48VDC
Input frequency	DC
Driver included	No
Surge protection	-
Inrush current	-
Inrush time	-
Power consumption tolerance	+/- 10%
Power factor	-
Beam angle	145°
Warranty period	3 years
HS code	85395000
Country of origin	People's Republic of China

#### **Ordering Information**

Description	SKU	Order code
TULEX-180-BASIC- AMBER	1000000264	
TULEX-180-BASIC- AMBER (10 pcs)		929002100592

#### **Spectral Output and Dimming Specifications**

Dimmable	Yes
Dimmable range	100% to 1%
Colour temperature (K)	2100K
CRI	>50
Flicker index [Pst]	<1
Stroboscopic effect [SVM]	0
Colour consistency [SDCM]	6

#### **Operating and Mechanical Specifications**

Operating temperature	-10°C to 40°C / 14°F to 104°F
Lumen maintenance L70B50 [h]	>50,000 hours
Lens material	PC/PMMA
Housing material	PC/PMMA
Diameter	16mm
Height	-
Length	1890mm (2530mm with cable)
Width	-
Mount / Adaptor	Steel wire using fixing clamps
Connection	Cables with snap-in connectors
Control interface	PWM
Product weight per piece	0.54 kg / 1.19 Lbs pc.

#### Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	No
СВ	Yes
Flammability mark	НВ
EU energy classification rating	Exempt
IEC protection class	Class III
IK impact rating	IK03
IP Code	IP69

## Contact us or learn more at: www.once.lighting

#### **ONCE Innovations Inc**

3955 Annapolis Ave N, Suite 100 Plymouth, MN 55447 P +1(763) 297 9163

#### **ONCE GmbH**

Vechtaer Marsch 3 49377 Vechta, Germany P +49 (0)4441 8898-10

Email: once.info@signify.com



© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change