

TULEX-180-PRO-W3000+Blue




- *Innovative tube light with wide beam angle*
- *Added blue spectrum can be used under system or as a catch light*
- *Improve animal welfare with full dimming and programming capabilities*
- *Durable and sustainable lighting solution*


Invest in the quality of your lighting system

Made to illuminate under systems with an added blue light spectrum, the TULEX-180-PRO-W3000+Blue LED tube light is an adaptable and easy-to-use fixture suitable for any operation. It features uniform light distribution, maximum durability, easy installation and improved animal welfare with its full dimming capabilities.

Dimensions



Beam Spread



Visit our website for more information: www.once.lighting

Specifications and Ordering

TULEX-180-PRO-W3000+Blue Specifications

Nominal power	4W / 2.7W
Luminous flux - human photopic	520 lm (ww), 64 lm (blue)
Luminous flux - poultry photopic	-
Initial LED luminaire efficacy	130 lm/W (ww), 22 lm/W (blue)
Input voltage	48VDC
Input frequency	DC
Driver included	No
Surge protection	-
Inrush current	-
Inrush time	-
Power consumption tolerance	+/- 10%
Power factor	-
Beam angle	145°
Warranty period	3 years
HS code	85395000
Country of origin	People's Republic of China

Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 1%
Colour temperature (K)	3000K
CRI	>80
Flicker index [Pst]	<1
Stroboscopic effect [SVM]	Exempt
Colour consistency [SDCM]	6

Operating and Mechanical Specifications


Operating temperature	-10°C to 40°C / 14°F to 104°F
Lumen maintenance L70B50 [h]	>50,000 hours
Lens material	PC/PMMA
Housing material	PC/PMMA
Diameter	16mm
Height	-
Length	1890mm (2530mm with cable)
Width	-
Mount / Adaptor	Steel wire using fixing clamps
Connection	Cables with snap-in connectors
Control interface	PWM
Product weight per piece	0.54 kg / 1.19 Lbs pc.

Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	No
CB	Yes
Flammability mark	HB
EU energy classification rating	E
IEC protection class	Class III
IK impact rating	IK03
IP Code	IP69

Ordering Information

Description	SKU	Order code
TULEX-180-PRO-W3000+Blue	1000000157	
TULEX-180-PRO-W3000+Blue (10 pcs)		929002100596



Contact us
or learn more at:
www.once.lighting

ONCE Innovations Inc

3955 Annapolis Ave N, Suite 100
Plymouth, MN 55447
P +1(763) 297 9163

ONCE GmbH

Vechtaer Marsch 3
49377 Vechta, Germany
P +49 (0)4441 8898-10

Email: once.info@signify.com

once
by **signify**

© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change