ONCE WHITE LED 2700K and 5000K | 230V

LIGHTING DESIGNED FOR ANIMALS

9W





High energy efficiency ~ 110 lm/w




Designed for tough barn environments



Dimmable from 1-100%



Simple 1:1 replacement with E27 fitting



BEAM SPREAD



SPECIFICATIONS & ORDERING

763-381-5621

Order code	1000001024	1000001030	
	929003965172	929003965183	
Nominal power	9W (5000K)	9W (2700K)	
Luminous flux - human photopic	1000 lm		
Initial LED luminaire efficacy	110 lm/W	110 lm/W	
Input voltage	220-240 V	220-240 V	
Input frequency	50Hz/60Hz	50Hz/60Hz	
Driver included	Yes	Yes	
Surge protection	750 V	750 V	
Inrush current	1.127A	1.127A	
Inrush time	0.071mS	0.071mS	
Power consumption tolerance	10%	10%	
Power factor	0.8	0.8	
Beam angle	150 Degrees	150 Degrees	
Warranty period	3 years		
HS code	8539520010		
Spectral Output and Dimming Specific	ations		
Dimmable	Yes, 1-100%		
Spectral Output	5000K	2700K	
Operating and Mechanical Specification	ons		
Operating temperature	-10°C to 40°C / 14°F to 104°F		
Rated life	L70 25k hours		
Lens material	PC		
Housing material	PA		
Diameter	60 mm		
Height	116 mm		
Length	60 mm		
Width	60 mm		
Mount/adapter and connection	E27 socket		
Control interface	Trailing edge dimming		
Product weight per piece	80g/0.176lbs	80g/0.176lbs	
Safety and Certifications			
CE Mark	Yes	Yes	
RoHS Compliant	Yes	Yes	
ECO energy classification	Class E		
IK and IP Rating	IK03 and IP65		



Our global brands are



